

In the Claims

Claims 1-73 (cancelled)

74. (currently amended) In a hand held non-contact temperature measurement instrument comprising on a common support the combination of an infrared radiation detector having a field of view coincident with a target surface temperature measurement area; and a laser system for aiming said detector at said target surface area;

the improvement in which said system includes ~~multiple~~ more than two independent spaced apart lasers, each of which directs ~~at least one~~ a visible laser beam onto said surface to indicate to the user a pattern of spaced apart light spots which identify the edges of the target surface ~~measurement area and location~~ measured by said detector.

75. (cancelled)

76. (cancelled)

77. (cancelled)

78. (cancelled)

79. (currently amended) An instrument according to claim 74 in which said ~~multiple~~ lasers direct separate spaced apart beams to the edges of the field of view of said detector.

80. (cancelled)

81. (currently amended) In a hand held temperature instrument having mounted on a common support a ~~radiometer~~ radiation detector having a longitudinal axis and a field of view; and a radiation detector laser sighting system mounted adjacent said detector;

the improvement in said sighting system wherein [[two]] more than two independent lasers are mounted respectively on ~~opposite~~ sides of the radiometer axis, and a separate beam from said each laser indicates visually on a target measurement surface ~~opposite~~ parts of the field of view of said detector.

82. (cancelled)

83. (cancelled)

84. (cancelled)

85. (cancelled)

86. (currently amended) A hand-held temperature measurement instrument comprising a radiometer having a field of view coincident with a target measurement surface area, and [[two]] more than two spaced apart mutually independent lasers for aiming said radiometer at said area, all mounted on a common support, each laser directing a visible laser beam onto said measurement surface area to display a pattern of spaced apart light spots which identify the edge and location of the field of view of said radiometer.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**